

SAFETY DATA SHEET

Classified in accordance with Health Canada Hazardous Products Regulations
(SOR/2015-17)

1. Identification

Product identifier:

DEGADUR® MDP Primer SG B

Recommended use of the chemical and restrictions on use**Recommended use:** bridge membrane system**Recommended restrictions:** None known.**Manufacturer/Importer/Distributor Information**

Company Name : Evonik Canada Inc.
3380 South Service Road
L7N 3J5 Burlington ON
Canada

Telephone : +1 905 336 3423

Fax : +1 905 332 5632

E-mail : product-regulatory-service@evonik.com

Emergency telephone number:

24-Hour Health : +1 800 424 9300 (CHEMTREC - US & CANADA)
Emergency : +1 800 681 9531 (CHEMTREC MEXICO)
+1 703 527 3887 (CHEMTREC WORLD)
+1 613 996 6666 (CANUTEC Canada)
+1 973 929 8060 (Product Regulatory Services)

2. Hazard(s) identification

Hazard Classification**According to Hazardous Product Regulations****Physical Hazards**

Flammable liquids Category 2

Health Hazards

Skin Corrosion/Irritation Category 2

Skin sensitizer Category 1

Specific Target Organ Toxicity -
Single Exposure Category 3¹**Target Organs**

1. Respiratory tract irritation.

Environmental HazardsAcute hazards to the aquatic
environment Category 3**Label Elements**

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Highly flammable liquid and vapor.
May cause flash fire or explosion.
Causes skin irritation.
May cause an allergic skin reaction.
May cause respiratory irritation.
Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/...] equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/eye protection/face protection.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water [or shower]. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see on this label). IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. In case of fire: Use... to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Keep cool.

Disposal: Dispose of contents/container in accordance with local regulation.

Physical Hazards Not Otherwise Classified: Classification not possible

Health Hazards Not Otherwise Classified: Classification not possible

3. Composition/information on ingredients

Mixtures

Chemical Identity	Common name and synonyms	CAS number	Content in percent (%)*
Methyl methacrylate		80-62-6	45 - 70%
triethyleneglycol dimethacrylate		109-16-0	1 - 5%
Triisodecylphosphite		25448-25-3	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition Comments: Solution of an acrylic polymer in an acrylic acid ester
Composition Comments: The exact concentration has been withheld as a trade secret.

4. First-aid measures
Description of necessary first-aid measures

General information: Take off all contaminated clothing immediately. Medical treatment is necessary if symptoms occur which are obviously caused by skin or eye contact with the product or by inhalation of its vapours.

Inhalation: Remove to fresh air. If breathing is difficult, get medical attention.

Skin Contact: Immediately wash skin with soap and plenty of water. Remove contaminated clothing and shoes. Obtain medical attention if irritation develops or persists. Wash clothing before reuse.

Eye contact: In case of contact, immediately flush eyes with plenty of water. Hold eyelids apart during flushing to ensure rinsing of the entire surface of the eye with water. Obtain medical attention if irritation develops or persists. **DO NOT WEAR CONTACT LENSES WHEN USING THIS PRODUCT.**

Ingestion: If swallowed, call a Poison Control Centre or doctor immediately. Do NOT induce vomiting.

Personal Protection for First-aid Responders: Evacuate enclosed and surrounding areas., As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear., Use water spray to cool containers exposed to fire and disperse vapors., Keep spills away from sources of ignition.

Most important symptoms/effects, acute and delayed

Symptoms: Skin sensitizerSkin irritationExcessive or prolonged exposure can cause the following:Headache.confusion

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: No

5. Fire-fighting measures

General Fire Hazards: Vapours are heavier than air and can form an explosive mixture with air. Flammable liquid. Vapors can travel to a source of ignition and flash back. Explosive mixtures may occur at temperatures at or above the flashpoint. Remove sources of ignition. Also keep emptied containers away from sources of heat and ignition. Keep out unprotected persons. In case of fire, remove the endangered barrels and bring to a safe place, if this can be done safely. Containers exposed to heat (fire) may build up pressure. Cool by splashing with water. Prevent fire extinguishing water from contaminating surface water or the ground water system. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: foam Dry chemical. Carbon dioxide water with wetting agent

Unsuitable extinguishing media: high volume water jet

Specific hazards arising from the chemical: May be released in case of fire: carbon monoxide, carbon dioxide, organic products of decomposition. Closed container may rupture if strongly heated. Vapours may form explosive mixtures with air. Combustible air-vapour mixtures are heavier than the air and spread along the floor. Ignition from a considerable distance is possible.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: Keep away from sources of ignition - No smoking. Vapors are heavier than air. Flammable liquid. Vapors can travel to a source of ignition and flash back. Explosive mixtures may occur at temperatures at or above the flashpoint. Take action to prevent static discharges. Use explosion-proof equipment. In the event of fire, cool the endangered containers with water. Fire fighting must be carried out from a safe distance.

Special protective equipment for fire-fighters: Evacuate enclosed and surrounding areas. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to cool containers exposed to fire and disperse vapors. Keep spills away from sources of ignition.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Assure sufficient ventilation. Use personal protective clothing. Keep away from sources of ignition. Use breathing apparatus if exposed to vapours/dust/mist/aerosol.

Methods and material for containment and cleaning up: Remove sources of ignition and ventilate area. Absorb spill with inert material and place in a chemical waste container. Obey relevant local, state, provincial and federal laws and regulations. Do not contaminate any lakes, streams, ponds, groundwater or soil. Use personal protective equipment. See Material Safety Data Sheet section 8, Exposure Controls/Personal Protection.

Environmental Precautions: Prevent product from getting into drains/surface water/groundwater.

7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation):	Provide general and/or local exhaust ventilation to maintain airborne levels below the exposure limits in Section 8. Refer to the current edition of 'Industrial Ventilation: A Manual of Recommended Practice' published by the American Conference of Government Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.
Safe handling advice:	<p>Keep away from sources of ignition - No smoking. Vapors are heavier than air. Flammable liquid. Vapors can travel to a source of ignition and flash back. Explosive mixtures may occur at temperatures at or above the flashpoint.</p> <p>Take action to prevent static discharges. Use explosion-proof equipment. In the event of fire, cool the endangered containers with water. Fire fighting must be carried out from a safe distance. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. A safety shower and eye wash fountain should be readily available. To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product. Product is supplied in a stabilized form. Keep away from heat. Keep away from sparks, flames and other sources of ignition. Use explosion proof equipment. Take precautionary measures against static discharges. Open container carefully as it may be pressurized. Use portable ventilation if necessary at job site. Ground and bond containers when transferring material. The need for grounding and bonding of containers in accordance with OSHA 29 CFR 1910.106 and NFPA 77 should be assessed for all product transfers. Keep container tightly closed. Do not eat, drink, smoke or chew tobacco around material. Use only with adequate ventilation. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Container hazardous when empty. Emptied container retains vapor and product residue. Follow all MSDS/label precautions even after the container is emptied. Residual vapors might explode on ignition; do not apply heat, cut, drill, grind or weld on or near this container.</p>
Contact avoidance measures:	No data available.
Hygiene measures:	Take off all contaminated clothing immediately. Store work clothing separately. Follow the usual good standards of occupational hygiene. Clean skin thoroughly after work; apply skin cream.
Storage	
Safe storage conditions:	Improper disposal or re-use of this container may be dangerous and illegal. Keep containers closed when not in use. Ensure there is good room ventilation. Limit storage of flammable liquids to approved areas equipped with overhead sprinklers. Protect material from contamination (refer to Section 10 for incompatibilities). Do not heat or cut the empty container with electric or gas torch. Keep in the original container at a temperature not exceeding 25 °C (77 °F). Keep away from heat. Keep away from sparks, flames and other sources of ignition. Keep locked up. Fill the container by approximately 90 % only as oxygen (air) is required for stabilisation. With large storage containers make sure the oxygen (air) supply is sufficient to ensure stability. Keep away from direct sunlight.
Safe packaging materials:	No data available.

8. Exposure controls/personal protection

Control Parameters Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values		Source
Methyl methacrylate	TWA	50 ppm	205 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	100 ppm	410 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Methyl methacrylate	TWA	50 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	STEL	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Methyl methacrylate		50 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2016)
		100 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2016)
Methyl methacrylate	TWA	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	STEL	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Methyl methacrylate	8 HR ACL	50 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL	100 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
Methyl methacrylate	TWA	50 ppm	205 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Methyl methacrylate	TWA	50 ppm		US. ACGIH Threshold Limit Values (03 2016)
	STEL	100 ppm		US. ACGIH Threshold Limit Values (03 2016)

Appropriate Engineering Controls

Provide general and/or local exhaust ventilation to maintain airborne levels below the exposure limits in Section 8. Refer to the current edition of 'Industrial Ventilation: A Manual of Recommended Practice' published by the American Conference of Government Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Individual protection measures, such as personal protective equipment

Eye/face protection: Use safety glasses (ANSI Z87.1 or approved equivalent).

Skin Protection

Hand Protection:

Material: butyl rubber gloves
 Break-through time: 60 min
 Guideline: EN 374
 Additional Information: Gloves should be replaced regularly, especially after extended contact with the product., For each work-place a suitable glove type has to be selected.

Other:

On handling of larger quantities: face mask, chemical-resistant boots and apron

Respiratory Protection:

A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 or applicable federal/provincial requirements must be followed whenever workplace conditions warrant respirator use. NIOSH's "Respirator Decision Logic" may be useful in determining the suitability of various types of respirators.

Hygiene measures: Take off all contaminated clothing immediately. Store work clothing separately. Follow the usual good standards of occupational hygiene. Clean skin thoroughly after work; apply skin cream.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	colourless
Odor:	ester-like
Odor Threshold:	< 1 ppm
pH:	Not applicable
Freezing point:	-48 °C (methyl methacrylate) -54.4 °F
Boiling Point:	approx. 100 °C (1,013 hPa) 100 °C (1,013 hPa)
Flash Point:	10 °C (DIN 51 755) (methyl methacrylate) 48 °F (Setaflash Closed Cup) (methyl methacrylate)
Evaporation Rate:	3.1 (butyl acetate = 1)
Flammability (solid, gas):	No data available.

Explosive limit - upper (%):	12.5 %(V) (methyl methacrylate)
Explosive limit - lower (%):	2.1 %(V) (methyl methacrylate)
Vapor pressure:	approx. 40 hPa (20 °C)
Vapor density (air=1):	> 1 20 °C 68 °F
Density:	1.02 g/cm ³ (20 °C) (68 °F) (DIN 51757)
Relative density:	No data available.
Solubility(ies)	
Solubility in Water:	approx. 16 g/l (methyl methacrylate)
Solubility (other):	soluble in most organic solvents
Partition coefficient (n-octanol/water):	Not available.
Self Ignition Temperature:	not pyrophoric
Decomposition Temperature:	This product is stable under normal storage conditions.
Kinematic viscosity:	No data available.
Dynamic viscosity:	50 - 100 mPa.s (23 °C) (73 °F, DIN 53015)
Other information	
Explosive properties:	No data available.
Oxidizing properties:	No data available.
Minimum ignition temperature:	430 °C (DIN 51794) (methyl methacrylate) 806 °F (DIN 51794) (methyl methacrylate)

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	This product is stable under normal storage conditions.
Possibility of hazardous reactions:	May occur when exposed to excessive heating or contaminated with incompatible materials.
Conditions to avoid:	Heat and ignition sources, aging, contamination, oxygen free atmosphere.
Incompatible Materials:	Peroxides, amines, sulfur compounds, heavy metal ions, alkalis, reducing agents and oxidizing agents.

Hazardous Decomposition Products: None when used as directed.

11. Toxicological information

Information on likely routes of exposure

Inhalation: Relevant route of exposure. Information on effects are given below.

Skin Contact: Relevant route of exposure. Information on effects are given below.

Eye contact: Relevant route of exposure. Information on effects are given below.

Ingestion: If handled correctly, not a relevant route of exposure. Information on effects are given below.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: Headache. Dizziness.

Skin Contact: May cause allergic skin reaction. May cause skin irritation.

Eye contact: Causes serious eye irritation.

Ingestion: If handled correctly, not a relevant route of exposure. Information on effects are given below.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.No data available.

Specified substance(s):

Methyl methacrylate LD 50 (Rat): > 5,000 mg/kg

triethyleneglycol dimethacrylate LD 50 (Rat): > 5,000 mg/kg

Triisodecylphosphite LD 50 (Rat): 13,800 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.No data available.

Specified substance(s):

Methyl methacrylate LD 50 (Rabbit): > 5,000 mg/kg

triethyleneglycol dimethacrylate LD 50 (Mouse): > 2,000 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.No data available.

Specified substance(s):
Methyl methacrylate LC 50 (Rat): 29.8 mg/l

Triisodecylphosphite LC 50 (Rat): > 12.6 mg/l

Repeated dose toxicity

Product: No data available.

Specified substance(s):
Methyl methacrylate NOAEL (Rat, Inhalation(Vapour)): 25 ppm
NOAEL (Rat, Oral): 2000 ppm
triethyleneglycol NOAEL (Rat, Oral): 1,000 mg/kg
dimethacrylate

Skin Corrosion/Irritation

Product: Contact with skin may cause irritations. Properties of components in summary.

Serious Eye Damage/Eye Irritation

Product: Contact with the eyes may cause irritation. Properties of components in summary.

Respiratory or Skin Sensitization

Product: No data available.

Specified substance(s):
Methyl methacrylate Local Lymph Node Assay, OECD TG 429 (Mouse): May cause sensitization by skin contact.
triethyleneglycol Local Lymph Node Assay (Mouse): Skin sensitizer
dimethacrylate
Triisodecylphosphite May cause sensitization by skin contact.

Carcinogenicity

Product: Contains no ingredient listed as a carcinogen (>0.1%).

Germ Cell Mutagenicity

In vitro
Product: No data available.

Specified substance(s):
triethyleneglycol Not classified
dimethacrylate

In vivo
Product: No data available.

Specified substance(s):
triethyleneglycol Not classified
dimethacrylate

Reproductive toxicity

Product: Contains no ingredient listed as toxic to reproduction (>0.1%).

Specific Target Organ Toxicity - Single Exposure

Product:	No data available.
Specified substance(s):	
Methyl methacrylate	Category 3 with respiratory tract irritation.
triethyleneglycol	Not classified
dimethacrylate	
Triisodecylphosphite	Not classified

Specific Target Organ Toxicity - Repeated Exposure

Product:	No data available.
Specified substance(s):	
Methyl methacrylate	Not classified
triethyleneglycol	Not classified
dimethacrylate	
Triisodecylphosphite	Not classified

Aspiration Hazard

Product: No aspiration toxicity classification

Other effects: Avoid contact with the skin and eyes and inhalation of the product vapours. There are no toxicological data available for the product as such.

12. Ecological information

Ecotoxicity:
Acute hazards to the aquatic environment:
Fish

Product:	No data available.
Specified substance(s):	
Methyl methacrylate	LC 50 (Oncorhynchus mykiss (rainbow trout), 96 h): > 79 mg/l NOEC (Danio rerio (zebra fish), 32 d): 9.4 mg/l literature
triethyleneglycol dimethacrylate	LC 50 (Danio rerio (zebra fish), 96 h): 16.4 mg/l

Aquatic Invertebrates

Product:	No data available.
Specified substance(s):	
Methyl methacrylate	EC 50 (Daphnia magna (Water flea), 48 h): 69 mg/l NOEC (Daphnia magna (Water flea), 21 d): 37 mg/l

Chronic hazards to the aquatic environment:
Fish

Product: No data available.

Aquatic Invertebrates

Product:	No data available.
Specified substance(s):	
triethyleneglycol dimethacrylate	NOEC (Daphnia magna (Water flea), 21 d): 32 mg/l

Toxicity to Aquatic Plants
Product: No data available.

Specified substance(s):

 Methyl methacrylate EC 50 (Selenastrum capricornutum (green algae), 72 h): > 100 mg/l
 NOEC (Selenastrum capricornutum (green algae), 72 h): > 100 mg/l

 triethyleneglycol EC 50 (Pseudokirchneriella subcapitata (green algae), 72 h): > 100 mg/l
 dimethacrylate NOEC (Pseudokirchneriella subcapitata (green algae), 72 h): 18.6 mg/l

Persistence and Degradability
Biodegradation
Product: (monomer constituent)

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: no evidence for hazardous properties

Partition Coefficient n-octanol / water (log Kow)
Product: Log Kow: Not available.

Mobility in soil:

no specific test data available

Other adverse effects:

Prevent substance from entering soil, natural bodies of water and sewer systems.

13. Disposal considerations

Disposal methods:

Waste must be disposed of in accordance with federal, state and local regulations. Incineration is the preferred method. Empty containers must be handled with care due to product residue. DO NOT HEAT OR CUT THE EMPTY CONTAINER WITH ELECTRIC OR GAS TORCH.

Contaminated Packaging:

No data available.

14. Transport information

Domestic regulation
TDG

 UN number : UN 1866
 Proper shipping name : RESIN SOLUTION

 Class : 3
 Packing group : II
 Labels : 3
 Marine pollutant : no

International Regulations
IATA-DGR

 UN/ID No. : UN 1866
 Proper shipping name : Resin solution STABILIZED
 Class : 3
 Packing group : II

Labels : 3
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code
UN number : UN 1866
Proper shipping name : RESIN SOLUTION STABILIZED

Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. Regulatory information

Canada Federal Regulations

List of Toxic Substances (CEPA, Schedule 1)

Not Regulated

Export Control List (CEPA 1999, Schedule 3)

Not Regulated

National Pollutant Release Inventory (NPRI)

Canada. National Pollutant Release Inventory (NPRI) Substances, Part 5, VOCs with Additional Reporting Requirements

NPRI PT5 Not Regulated

Canada. National Pollutant Release Inventory (NPRI) (Schedule 1, Parts 1-4)

NPRI Methyl methacrylate

Greenhouse Gases

Not Regulated

Canada. Substances Subject to Significant New Activity (SNAc) Reporting Requirements

Not Regulated

Controlled Drugs and Substances Act

CA CDSI Not Regulated

CA CDSII Not Regulated

CA CDSIII Not Regulated

CA CDSIV Not Regulated

CA CDSV Not Regulated

CA CDSVII Not Regulated

CA CDSVIII Not Regulated

Precursor Control Regulations

Not Regulated

Inventory Status:

Registration, Evaluation and Authorisation of Chemicals (REACH):	preregistered, registered or exempted
US TSCA Inventory:	On or in compliance with the inventory
Canada DSL Inventory List:	On or in compliance with the inventory
Canada NDSL Inventory:	Not on Inventory.
Australia AICS:	On or in compliance with the inventory
Japan (ENCS) List:	On or in compliance with the inventory
Korea Existing Chemicals Inv. (KECI):	On or in compliance with the inventory
Philippines PICCS:	On or in compliance with the inventory
China Inv. Existing Chemical Substances:	On or in compliance with the inventory

16. Other information, including date of preparation or last revision

Issue Date:	07/16/2019
Revision Date:	07/03/2019: ARGLO_SUBTYP07/03/2019: ARGLO_EXCOMP07/03/2019: ARGHS_DOC07/03/2019: ARGHS_HZ_ING07/03/2019: ARCA_COMP07/03/2019: ARGLO_REG07/09/2019: ARCA_SEC15
Version #:	1.2
Further Information:	No data available.
Revision Information:	Changes since the last version are highlighted in the margin. This version replaces all previous versions.
Disclaimer:	This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.