

# Safety Data Sheet

OSHA 1910.1200  
Revision Date: 05/27/2015  
Print Date: 06/05/2015  
Version: 4.1



**DEGAROUTE® 460 Binder Resin**

Page 1 of 18

## 1. Product and Company Identification

### 1.1. Product identifier

Trade name : **DEGAROUTE® 460 Binder Resin**

Solution of an acrylic polymer in methacrylic acid esters / acrylic acid esters

### 1.2. Recommended use of the chemical and restrictions on use

Recommended use(s): binder for road marking

Non-recommended use(s): None known.

### 1.3. Details of the supplier of the safety data sheet

Evonik Corporation USA  
299 Jefferson Road  
Parsippany, NJ 07054-0677  
USA

973-929-8000  
973-929-8040 (fax)

product-regulatory-services@evonik.com

Product Information Number 973-929-8060  
24 Hour Emergency Number, CHEMTREC 1-800-424-9300

## 2. Hazards identification

### 2.1. Classification of the substance or mixture

This mixture is classified as hazardous according to US-GHS.

#### Classification according to Regulation 29CFR 1910.1200

Flammable liquids	Hazard category 2	H225
Caustic burning / irritation of skin	Hazard category 2	H315
Skin Sensitisation	Hazard category 1 B	H317
Specific Target Organ Toxicity - Single exposure	Hazard category 3	H335
Carcinogenicity	Hazard category 1 B	H350

### 2.2. Label elements

GHS pictogram



Signal word

**Danger**

# Safety Data Sheet

OSHA 1910.1200

Revision Date: 05/27/2015

Print Date: 06/05/2015

Version: 4.1



## DEGAROUTE® 460 Binder Resin

Page 2 of 18

Hazard statement	Highly flammable liquid and vapour. (H225) Causes skin irritation. (H315) May cause an allergic skin reaction. (H317) May cause respiratory irritation. (H335) May cause cancer. (H350)
Safety notice (general)	Wear protective gloves/protective clothing/eye protection. (P280)
Precautionary Statement (Prevention)	Obtain special instructions before use. (P201) Do not handle until all safety precautions have been read and understood. (P202) Keep away from heat/sparks/open flames/hot surfaces. - No smoking. (P210) Keep container tightly closed. (P233) Ground/bond container and receiving equipment. (P240) Use explosion-proof electrical/ ventilating/ lighting/ equipment. (P241) Use only non-sparking tools. (P242) Take precautionary measures against static discharge. (P243) Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. (P261) Wash hands thoroughly after handling. (P264) Use only outdoors or in a well-ventilated area. (P271) Contaminated work clothing should not be allowed out of the workplace. (P272)
Precautionary Statement (Response)	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. (P303 + P361 + P353) IF INHALED: Remove person to fresh air and keep comfortable for breathing. (P304 + P340) IF exposed or concerned: Get medical advice/ attention. (P308 + P313) Call a POISON CENTER or doctor/ physician if you feel unwell. (P312) Specific treatment (see supplemental first aid instructions on this label). (P321) If skin irritation or rash occurs: Get medical advice/ attention. (P333 + P313) Take off contaminated clothing and wash before reuse. (P362) In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction. (P370 + P378)
Precautionary Statement (Storage)	Store in a well-ventilated place. Keep container tightly closed. (P403 + P233) Keep cool. (P235) Store locked up. (P405)
Precautionary Statement (Disposal)	Dispose of contents/container according to the local / regional/national/international waste disposal regulations. (P501)
Hazardous component(s) for labelling	contains methyl methacrylate 2-ethylhexyl acrylate N,N-dimethyl-p-toluidine

### 2.3. Other hazards

# Safety Data Sheet

OSHA 1910.1200  
Revision Date: 05/27/2015  
Print Date: 06/05/2015  
Version: 4.1



DEGAROUTE® 460 Binder Resin

Page 3 of 18

electrostatic charge

The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is exceeded, the product may polymerize with heat evolution.

## 3. Composition/information on ingredients

### 3.1. Substances

---

### 3.2. Mixtures

#### Hazardous Ingredients

Component	CAS-No.	Content	Hazard class / Hazard category / Hazard statement
methyl methacrylate	80-62-6	30.0 - 60.0 %	Flam. Liq. 2 ; H225 Skin Irrit. 2 ; H315 Skin Sens. 1B ; H317 STOT SE 3 ; H335
2-ethylhexyl acrylate	103-11-7	15.0 - 40.0 %	Flam. Liq. 4 ; H227 Skin Irrit. 2 ; H315 Skin Sens. 1B ; H317 STOT SE 3 (inhalation); H335
N,N-dimethyl-p-toluidine	99-97-8	0.1 - 1.0 %	Flam. Liq. 4 ; H227 Acute Tox. 3 (oral); H301 Acute Tox. 3 (dermal); H311 Acute Tox. 3 (inhalation); H331 Carc. 1B ; H350 STOT RE 2 ; H373

## 4. First-aid measures

### 4.1. Description of first aid measures

General advice	Take off all contaminated clothing immediately. Medical treatment is necessary if symptoms occur which are obviously caused by skin or eye contact with the product or by inhalation of its vapours.
Inhalation	Move subject to fresh air and keep him calm. Seek medical advice immediately.
Skin contact	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before re-use. Contact a doctor immediately.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids. Seek medical advice immediately.
Ingestion	Do not induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person.

### 4.2. Most important symptoms and effects, both acute and delayed

# Safety Data Sheet

OSHA 1910.1200  
Revision Date: 05/27/2015  
Print Date: 06/05/2015  
Version: 4.1



**DEGAROUTE® 460 Binder Resin**

Page 4 of 18

Excessive or prolonged exposure can cause the following: , Headache, confusion, irritation, Product has dermal defatting effect

### 4.3. Indication of any immediate medical attention and special treatment needed

No specific antidote known.  
Symptomatic treatment.

## 5. Fire-fighting measures

### 5.1. Extinguishing media

Suitable extinguishing media      foam, dry chemical, carbon dioxide  
Unsuitable extinguishing media      High volume water jet

### 5.2. Specific hazards arising from the chemical

May be released in case of fire: carbon monoxide, carbon dioxide, organic products of decomposition. Closed container may rupture if strongly heated. Vapours may form explosive mixtures with air. Combustible air-vapour mixtures are heavier than the air and spread along the floor. Ignition from a considerable distance is possible.

### 5.3. Special protective equipment and precautions for fire-fighters

Evacuate enclosed and surrounding areas. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to cool containers exposed to fire and disperse vapors. Keep spills away from sources of ignition.

Vapours are heavier than air and can form an explosive mixture with air. Flammable liquid. Vapors can travel to a source of ignition and flash back. Explosive mixtures may occur at temperatures at or above the flashpoint.

Remove all sources of ignition. Also keep emptied containers away from sources of heat and ignition. Keep out unprotected persons. In case of fire, remove the endangered barrels and bring to a safe place, if this can be done safely. Containers exposed to heat (fire) may build up pressure. Cool by splashing with water. Prevent fire extinguishing water from contaminating surface water or the ground water system. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Assure sufficient ventilation. Use personal protective clothing. Use breathing apparatus if exposed to vapours/dust/mist/aerosol. Keep away from open flames, hot surfaces and sources of ignition. Vapours can form explosive mixtures with air. Keep out unprotected persons. Avoid spark generation.

### 6.2. Environmental precautions

Prevent product from getting into drains/surface water/groundwater.

# Safety Data Sheet

OSHA 1910.1200  
Revision Date: 05/27/2015  
Print Date: 06/05/2015  
Version: 4.1



**DEGAROUTE® 460 Binder Resin**

Page 5 of 18

## 6.3. Methods and materials for containment and cleaning up

Remove sources of ignition and ventilate area. All equipment used when handling the product must be grounded. Absorb spill with inert material and place in a chemical waste container. Obey relevant local, state, provincial and federal laws and regulations. Larger quantities: Remove mechanically (by pumping). Use explosion-proof equipment!

## 6.4. Reference to other sections

For personal protection see section 8.

## 7. Handling and storage

### 7.1. Precautions for safe handling

Safe handling advice

Use only trained personnel. Remove contaminated clothing and wash it before reuse. Product is supplied in a stabilized form. Keep locked up. Keep away from heat. Keep away from sparks, flames and other sources of ignition. Use explosion proof equipment. Take precautionary measures against static discharges. Open container carefully as it may be pressurized. Use portable ventilation if necessary at job site. Ground and bond containers when transferring material. The need for grounding and bonding of containers in accordance with OSHA 29 CFR 1910.106 and NFPA 77 should be assessed for all product transfers. Keep container tightly closed. Do not eat, drink, smoke or chew tobacco around material. Use only with adequate ventilation. Avoid breathing vapor or mist. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Container hazardous when empty. Emptied container retains vapor and product residue. Follow all MSDS/label precautions even after the container is emptied. Residual vapors might explode on ignition; do not apply heat, cut, drill, grind or weld on or near this container.

Advice on protection against fire and explosion

Keep away from sources of ignition --- No smoking. Vapors are heavier than air. Flammable liquid. Vapors can travel to a source of ignition and flash back. Explosive mixtures may occur at temperatures at or above the flashpoint.  
Take precautionary measures against static discharges. Use only explosion-proof equipment. In the event of fire, cool the endangered containers with water. Fire fighting must be carried out from a safe distance.

### 7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container closed when not in use. Ensure there is good room ventilation. Limit storage of flammable liquids to approved areas equipped with overhead sprinklers. Protect material from contamination (refer to Section 10 for incompatibilities). Residual vapors might explode on ignition; do not apply heat, cut, drill, grind or weld on or near this container. Do not heat or cut the empty container with electric or gas torch. Keep in the original container at a temperature not exceeding 30 °C (86 °F). Keep away from heat. Keep away from sparks, flames and other sources of ignition. Keep locked up. Fill the container by approximately 90 % only as oxygen (air) is required for stabilisation. With large storage containers make sure the oxygen (air) supply is sufficient to ensure stability.

Further information

Improper disposal or re-use of this container may be dangerous and illegal.

# Safety Data Sheet

OSHA 1910.1200  
Revision Date: 05/27/2015  
Print Date: 06/05/2015  
Version: 4.1



DEGAROUTE® 460 Binder Resin

Page 6 of 18

## 8. Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure Limit Information

##### METHYL METHACRYLATE

(CAS Number 80-62-6)

Carcinogen designation(s) USA: EPA-NL; IARC-3; TLV-A4

Occupational Exposure Values

Remark(s):

ACGIH TLV-TWA	50 ppm	205 mg/m <sup>3</sup>	Sensitiser
ACGIH TLV-STEL	100 ppm	410 mg/m <sup>3</sup>	Sensitiser
OSHA PEL-TWA	100 ppm	410 mg/m <sup>3</sup>	
OSHA PEL-STEL			not established
OEL-TWA (Alberta)	50 ppm	205 mg/m <sup>3</sup>	
OEL-STEL (Alberta)	100 ppm	410 mg/m <sup>3</sup>	
OEL-TWA (British Columbia)	50 ppm		Capable of causing respiratory, dermal or conjunctival sensitization.
OEL-STEL (British Columbia)	100 ppm		Capable of causing respiratory, dermal or conjunctival sensitization.
OEL-TWA (Ontario)	50 ppm		
OEL-STEL (Ontario)	100 ppm		
OEL-TWA (Quebec)	50 ppm	205 mg/m <sup>3</sup>	Sensitiser
OEL-STEL (Quebec)			not established
OEL-TWA (Mexico)	100 ppm	410 mg/m <sup>3</sup>	Carcinogen Category 4 - not classifiable as a human carcinogen
OEL-STEL (Mexico)	125 ppm	510 mg/m <sup>3</sup>	Carcinogen Category 4 - not classifiable as a human carcinogen
OEL-STEL (Saskatchewan)	100 ppm		The product may cause sensitization.
OEL-TWA (Saskatchewan)	50 ppm		The product may cause sensitization.
OEL-STEL (Manitoba)	100 ppm		Sensitiser
OEL-TWA (Manitoba)	50 ppm		Sensitiser

# Safety Data Sheet

OSHA 1910.1200

Revision Date: 05/27/2015

Print Date: 06/05/2015

Version: 4.1



DEGAROUTE® 460 Binder Resin

Page 7 of 18

## 2-ETHYLHEXYL ACRYLATE

(CAS Number 103-11-7)

### Occupational Exposure Values

ACGIH TLV-TWA

ACGIH TLV-STEL

OSHA PEL-TWA

OSHA PEL-STEL

NIOSH REL-TWA

NIOSH REL-STEL

OEL-TWA (North Carolina)

OEL-STEL (North Carolina)

OEL-TWA (Alberta)

OEL-STEL (Alberta)

OEL-TWA (British Columbia)

OEL-STEL (British Columbia)

OEL-TWA (Ontario)

OEL-STEL (Ontario)

OEL-TWA (Quebec)

OEL-STEL (Quebec)

Short-Term ESL:

Annual ESL:

0.35 mg/m<sup>3</sup>

0.035

mg/m<sup>3</sup>

### Remark(s):

not established

## N,N-BIS-(2-HYDROXYPROPYL)-P-TOLUIDINE

(CAS Number 38668-48-3)

### Occupational Exposure Values

ACGIH TLV-TWA

ACGIH TLV-STEL

OSHA PEL-TWA

OSHA PEL-STEL

NIOSH REL-TWA

NIOSH REL-STEL

OEL-TWA (North Carolina)

OEL-STEL (North Carolina)

OEL-TWA (Alberta)

OEL-STEL (Alberta)

OEL-TWA (British Columbia)

OEL-STEL (British Columbia)

OEL-TWA (Ontario)

OEL-STEL (Ontario)

OEL-TWA (Quebec)

OEL-STEL (Quebec)

OEL-TWA (Mexico)

OEL-STEL (Mexico)

### Remark(s):

not established

# Safety Data Sheet

OSHA 1910.1200

Revision Date: 05/27/2015

Print Date: 06/05/2015

Version: 4.1



DEGAROUTE® 460 Binder Resin

Page 8 of 18

## N,N-DIMETHYL-P-TOLUIDINE

(CAS Number 99-97-8)

### Occupational Exposure Values

ACGIH TLV-TWA	
ACGIH TLV-STEL	
OSHA PEL-TWA	
OSHA PEL-STEL	
NIOSH REL-TWA	
NIOSH REL-STEL	
OEL-TWA (North Carolina)	
OEL-STEL (North Carolina)	
OEL-TWA (Alberta)	
OEL-STEL (Alberta)	
OEL-TWA (British Columbia)	
OEL-STEL (British Columbia)	
OEL-TWA (Ontario)	
OEL-STEL (Ontario)	
OEL-TWA (Quebec)	
OEL-STEL (Quebec)	
OEL-TWA (Mexico)	
OEL-STEL (Mexico)	
AIHA WEELs-TWA	0.5 ppm
Short-Term ESL:	90
Annual ESL:	9

### Remark(s):

not established  
not established

## TRIMETHYLOLPROPANE TRIMETHACRYLATE

(CAS Number 3290-92-4)

### Occupational Exposure Values

ACGIH TLV-TWA	
ACGIH TLV-STEL	
OSHA PEL-TWA	
OSHA PEL-STEL	
OEL-TWA (Alberta)	
OEL-STEL (Alberta)	
OEL-TWA (British Columbia)	
OEL-STEL (British Columbia)	
OEL-TWA (Ontario)	
OEL-STEL (Ontario)	
OEL-TWA (Quebec)	
OEL-STEL (Quebec)	
OEL-TWA (Mexico)	
OEL-STEL (Mexico)	
AIHA WEELs-TWA	1 mg/m3

### Remark(s):

not established  
Skin contact can invalidate limit values.  
Avoid skin or eye contact with liquids or aerosols.

# Safety Data Sheet

OSHA 1910.1200  
Revision Date: 05/27/2015  
Print Date: 06/05/2015  
Version: 4.1



## PARAFFIN FUME )

Occupational Exposure Values		Remark(s):
OEL-TWA (Ontario)	2 mg/m3	
OEL-STEL (Ontario)		not established
OEL-TWA (Quebec)	2 mg/m3	
OEL-STEL (Quebec)		not established
OEL-TWA (Mexico)	2 mg/m3	
OEL-STEL (Mexico)	6 mg/m3	
ACGIH TLV-TWA	2 mg/m3	
ACGIH TLV-STEL		not established
OSHA PEL-TWA		not established
OSHA PEL-STEL		not established
OEL-TWA (Alberta)	2 mg/m3	
OEL-STEL (Alberta)		not established
OEL-TWA (British Columbia)	2 mg/m3	
OEL-STEL (British Columbia)		not established
OEL-TWA (Tennessee)	2 mg/m3	
OEL-TWA (Oregon)	1 mg/m3	

## 8.2. Exposure controls

### Engineering controls

Provide general and/or local exhaust ventilation to maintain airborne levels below the exposure limits in Section 8. Refer to the current edition of 'Industrial Ventilation: A Manual of Recommended Practice' published by the American Conference of Government Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

## 8.3. Personal protective equipment

Protective measures	Avoid breathing vapor or mist. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. A safety shower and eye wash fountain should be readily available. To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product.
Hygiene measures	Take off all contaminated clothing immediately. Store work clothing separately. Follow the usual good standards of occupational hygiene. Clean skin thoroughly after work; apply skin cream.
Respiratory protection	A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 or applicable federal/provincial requirements must be followed whenever workplace conditions warrant respirator use. NIOSH's "Respirator Decision Logic" may be useful in determining the suitability of various types of respirators.
Hand protection	butyl rubber gloves (0.33 mm), Break through time ca. 66 min (EN 374) In practice, due to variable exposure conditions, this information can only be an aid to orientation for the selection of a suitable chemical protection glove. In particular, this information does not substitute suitability tests by the end user.

# Safety Data Sheet

OSHA 1910.1200  
Revision Date: 05/27/2015  
Print Date: 06/05/2015  
Version: 4.1



**DEGAROUTE® 460 Binder Resin**

Page 10 of 18

Splash protection	nitrile rubber gloves (minimal thickness 0.11 mm)
General information	Gloves should be replaced regularly, especially after extended contact with the product. For each work-place a suitable glove type has to be selected.
Eye protection	Use safety glasses (ANSI Z87.1 or approved equivalent).
Skin and body protection	Use chemically resistant apron or other impervious clothing to avoid prolonged or repeated skin contact.

## 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Colour	colourless, turbid
Form	liquid
Odor	ester-like
Odour Threshold	<1 ppm
physical state	liquid
Melting point/freezing point	no data available
Boiling point/range	ca. 100 °C (1,013 hPa) ca. 212 °F
Flash point	10 °C (DIN 51755) (methyl methacrylate) 50 °F
Evaporation rate	> 1 (butyl acetate = 1)
Ignition temperature	430 °C (DIN 51794) (methyl methacrylate) 806 °F
Autoignition temperature	no data available
Decomposition temperature	This product is stable under normal storage conditions.
Impact Sensitivity	Not impact sensitive.
Lower explosion limit	2.1 %(V) at 10,5°C / 33,8°F(methyl methacrylate)

# Safety Data Sheet

OSHA 1910.1200  
Revision Date: 05/27/2015  
Print Date: 06/05/2015  
Version: 4.1



**DEGAROUTE® 460 Binder Resin**

Page 11 of 18

Upper explosion limit	12.5 %(V) (methyl methacrylate)
Flammability (solid, gas)	no data available
Vapour pressure	ca. 40 hPa (= mbar) at 20 °C / 68 °F
Density	0.97 g/cm <sup>3</sup> at 20 °C / 68 °F ( DIN 51757 )
Relative density	no data available
Relative vapour density (related to air)	> 1 (20 °C) (68 °F)
Solubility in water	ca. 20 g/l at 20 °C / 68 °F
Fat solubility	no data available
Solubility (quantitative)	no data available
Solubility (qualitative)	no data available
pH	no data available
n-Octanol/water partition coefficient	no data available
Viscosity (dynamic)	ca. 230 mPa·s at 23 °C / 73 °F (Brookfield )
Viscosity (kinematic)	no data available

## 9.2. Other information

none

---

## 10. Stability and reactivity

### 10.1. Reactivity

see section 10.2.

### 10.2. Chemical stability

This product is stable under normal storage conditions.

### 10.3. Possibility of hazardous reactions

# Safety Data Sheet

OSHA 1910.1200  
Revision Date: 05/27/2015  
Print Date: 06/05/2015  
Version: 4.1



DEGAROUTE® 460 Binder Resin

Page 12 of 18

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

Vigorous polymerization is possible when heated /exposed to heat.

## 10.4. Conditions to avoid

Avoid high temperatures and sources of ignition. Ultraviolet light.

The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is exceeded, the product may polymerize with heat evolution.

## 10.5. Incompatible materials

Peroxides, amines, sulfur compounds, heavy metal ions, alkalis, reducing agents and oxidizing agents.

## 10.6. Hazardous decomposition products

None when used as directed.

## 11. Toxicological information

### 11.1. Information on toxicological effects

toxicokinetics, metabolism and distribution	no specific test data available	
Acute Oral Toxicity	LD50 rat, OECD 401	> 5,000 mg/kg
	Related to substance: methyl methacrylate LD50 rat	> 2,000 mg/kg
	Related to substance: 2-ethylhexyl acrylate	
Acute Inhalational Toxicity	LC50 rat, 4 h	29.8 mg/l
	Related to substance: methyl methacrylate LCLo Mouse	0.6 mg/l
	Related to substance: 2-ethylhexyl acrylate	
Acute Dermal Toxicity	LD50 rabbit	> 5,000 mg/kg
	Related to substance: methyl methacrylate LD50 rabbit	> 5,000 mg/kg
	Related to substance: 2-ethylhexyl acrylate	
Caustic burning / irritation of skin	Properties of components in summary. Related to substance: product	irritating
Serious eye damage/eye irritation	Contact with the eyes may cause irritation. Properties of components in summary. Related to substance: product	
Respiratory/skin sensitization		

# Safety Data Sheet

OSHA 1910.1200  
Revision Date: 05/27/2015  
Print Date: 06/05/2015  
Version: 4.1



DEGAROUTE® 460 Binder Resin

Page 13 of 18

	<p>In sensitization tests on guinea pigs with and without adjuvant, both positive and negative results were found. In humans various types of allergic reactions have been observed (symptoms: headache, eye irritations, skin affections). Related to substance: methyl methacrylate</p> <p>May cause sensitisation by skin contact. Related to substance: 2-ethylhexyl acrylate</p>
Aspiration hazard	not applicable
Mutagenicity assessment	<p>Positive as well as negative results in <i>in vitro</i> mutagenicity/ genotoxicity tests. No experimental indication of genotoxicity <i>in vivo</i> available. In summary not mutagenic according to internationally accepted criteria. Related to substance: methyl methacrylate</p>
Carcinogenicity	<p>There is evidence of carcinogenic effects. Carcinogen Category 1B (UN-GHS) Related to substance: N,N-dimethyl-p-toluidine Non-carcinogenic in inhalation and feeding studies carried out on rats, mice and dogs. Related to substance: methyl methacrylate Several long-term skin painting studies for carcinogenicity in mice were conducted and gave contradictory results. On the basis of all existing information no definite conclusion on a cancerogenic activity can be drawn. Related to substance: 2-ethylhexyl acrylate</p>
Reprotoxicity / teratogenicity	<p>No indications of teratogenic effects in experimental animals. Related to substance: methyl methacrylate</p>
CMR assessment	CMR: no
Toxicity on Repeated Administration	<p>rat, inhalation, 2 Years Findings: Damage to mucous membranes in the nose at 400 ppm Related to substance: methyl methacrylate NOAEL 25 ppm</p> <p>rat, in drinking water, 2 Years Findings: no toxic effects Related to substance: methyl methacrylate NOAEL 2000 ppm</p>
General information	<p>There are no toxicological data available for the product as such. Avoid contact with the skin and eyes and inhalation of the product vapours.</p>

## 12. Ecological information

### 12.1. Toxicity

Aquatic toxicity, fish	<p>LC50 <i>Oncorhynchus mykiss</i>, rainbow trout, OECD 203, flow through, GLP, 96 h Related to substance: methyl methacrylate &gt; 79 mg/l</p> <p>LC50 rainbow trout, 96 h Related to substance: trimethylol propane trimethacrylate 2 mg/l</p>
Aquatic toxicity, invertebrates	<p>EC50 <i>Daphnia magna</i>, OECD 202, flow through, 48 h Related to substance: methyl methacrylate 69 mg/l</p>

# Safety Data Sheet

OSHA 1910.1200  
Revision Date: 05/27/2015  
Print Date: 06/05/2015  
Version: 4.1



DEGAROUTE® 460 Binder Resin

Page 14 of 18

	NOEC Daphnia magna, OECD 202 part 2, flow through, 21 d	37 mg/l
	Related to substance: methyl methacrylate EC50 Daphnia magna, OECD 202 / ISO 6341 / 84/449/EEC V, C2, 48 h	17.5 mg/l
	Related to substance: 2-ethylhexyl acrylate	
Aquaticity, algae / aquatic plants	EC3 Scenedesmus quadricauda, cell proliferation inhibition test, 8 d	37 mg/l
	Related to substance: methyl methacrylate	
Toxicity in microorganisms	EC0 Pseudomonas putida	100 mg/l
	Related to substance: methyl methacrylate	

## 12.2. Persistence and degradability

Persistence and degradability no evidence for hazardous properties  
Biodegradability biodegradable (monomer constituent)

## 12.3. Bioaccumulative potential

Bioaccumulation no evidence for hazardous properties

## 12.4. Mobility in soil

Mobility no evidence for hazardous properties

## 12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment PBT: no  
vPvB: no

## 12.6. Other adverse effects

General Information Prevent substance from entering soil, natural bodies of water and sewer systems. Harmful to aquatic life with long lasting effects.

## 13. Disposal considerations

### 13.1. Waste treatment methods

Product Waste must be disposed of in accordance with federal, state and local regulations. Incineration is the preferred method. Empty containers must be handled with care due to product residue. DO NOT HEAT OR CUT THE EMPTY CONTAINER WITH ELECTRIC OR GAS TORCH.

Uncleaned packaging Contaminated packaging should ideally be emptied; it can then be recycled after having been decontaminated. Packaging that cannot be cleaned should be disposed of professionally. Uncontaminated packaging may be taken for recycling.

Do not reuse containers.

# Safety Data Sheet

OSHA 1910.1200  
Revision Date: 05/27/2015  
Print Date: 06/05/2015  
Version: 4.1



DEGAROUTE® 460 Binder Resin

Page 15 of 18

## 14. Transport information

### US DOT Hazard Classification

ID/UN Number 1866  
Proper Shipping Name RESIN SOLUTION  
Hazard Class 3  
Packing Group II  
ERG: 127

### Canadian TDG Classification

Refer to the classification US DOT

### Shipment by sea IMDG/GGVSee

UN number 1866  
Proper Shipping Name RESIN SOLUTION  
Class 3  
Packaging group II  
EmS F-E, S-E  
Marine pollutant No

### Air transport ICAO/IATA

UN number 1866  
Proper Shipping Name RESIN SOLUTION  
Class 3  
Packing Group II

## 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### INVENTORY INFORMATION

REACH (EU)	preregistered, registered or exempted
TSCA (USA)	listed or exempted
DSL (CDN)	listed or exempted
AICS (AUS)	listed or exempted
METI (J)	listed or exempted
ECL (KOR)	listed or exempted
PICCS (RP)	listed or exempted
IECSC (CN)	listed or exempted
ECS (Taiwan)	listed or exempted

#### US FEDERAL REGULATORY INFORMATION

Component / CASRN	TPQ [lbs]	CERCLA RQ [lbs] (40CFR302.4)	SARA 302 List of EHS	SARA 313 (40CFR372)	TSCA 12b
methyl methacrylate / 80-62-6	NONE	1000	NO	YES	NO

#### COMPONENT CLASSIFICATION UNDER CLEAN AIR ACT SECTION 112

Component / CASRN	Weight %	HAP	EHAP
methyl methacrylate / 80-62-6	30 - 60	YES	NO

# Safety Data Sheet

OSHA 1910.1200  
Revision Date: 05/27/2015  
Print Date: 06/05/2015  
Version: 4.1



## PRODUCT CLASSIFICATION UNDER SECTION 311/312 OF SARA (40CFR370)

ACUTE, CHRONIC, FIRE,

## US STATE REGULATORY INFORMATION

Component / CASRN	New Jersey RTK	Pennsylvania RTK	Massachusetts RTK	California Proposition 65 Cancer	California Proposition 65 Reproductive
methyl methacrylate / 80-62-6	YES	YES	YES	NO	NO
2-ethylhexyl acrylate / 103-11-7	YES	YES	YES	NO	NO
methacrylic acid ester / trade secret	NO	NO	NO	NO	NO
acrylic polymer	NO	NO	NO	NO	NO
paraffin / trade secret	YES	YES	YES	NO	NO
N,N-dimethyl-p-toluidine / 99-97-8	NO	NO	NO	YES	NO

This product contains (a) chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

## CANADIAN REGULATION

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation and the MSDS contains all information required by the Controlled Products Regulations.

This is a controlled product.  
**WHMIS:**B2, D2A, D2B

Component / CASRN	NPRI
methyl methacrylate / 80-62-6	YES
2-ethylhexyl acrylate / 103-11-7	NO

## 16. Other information

	Health	Flammability	Physical Hazard
HMIS-Ratings	2*	3	2
NFPA-Ratings	2	3	2

HMIS Hazard Ratings                      NFPA Hazard Ratings

# Safety Data Sheet

OSHA 1910.1200

Revision Date: 05/27/2015

Print Date: 06/05/2015

Version: 4.1



DEGAROUTE® 460 Binder Resin

Page 17 of 18

4 = severe	4 = extreme
3 = serious	3 = high
2 = moderate	2 = moderate
1 = slight	1 = slight
0 = minimal	0 = insignificant
N = no rating for powders	N = no rating for powders
* = chronic health hazard	

Relevant H phrases from chapter 3	methyl methacrylate
	H225 Highly flammable liquid and vapour.
	H315 Causes skin irritation.
	H317 May cause an allergic skin reaction.
	H335 May cause respiratory irritation.
	2-ethylhexyl acrylate
	H227 Combustible liquid.
	H315 Causes skin irritation.
	H317 May cause an allergic skin reaction.
	H335 May cause respiratory irritation.
	N,N-dimethyl-p-toluidine
	H301 Toxic if swallowed.
	H311 Toxic in contact with skin.
	H331 Toxic if inhaled.
	H350 May cause cancer.
	H373 May cause damage to organs through prolonged or repeated exposure.

References	relevant manuals and publications own examinations own toxicological and ecotoxicological studies toxicological and ecotoxicological studies of other manufacturers SIAR OECD-SIDS RTK public files
Revision Date	05/27/2015

Places marked by || have been amended from the last version.

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice., ® is a registered trademark

Date of printing : 06/05/2015

# Safety Data Sheet

OSHA 1910.1200

Revision Date: 05/27/2015

Print Date: 06/05/2015

Version: 4.1



## Legend

<b>ACC</b>	American Chemistry Council
<b>ACGIH</b>	American Conference of Governmental Industrial Hygienists
<b>ACS</b>	Advisory Committee on Sustainability
<b>ADI</b>	Acceptable Daily Intake
<b>ASTM</b>	American Society for Testing and Materials
<b>ATP</b>	Adaptation to Technical Progress
<b>BCF</b>	Bioconcentration factor
<b>BOD</b>	Biochemical oxygen demand
<b>c.c.</b>	closed cup
<b>CAO</b>	Cargo Aircraft Only
<b>Carc</b>	Carcinogen
<b>CAS</b>	Chemical Abstract Services
<b>CDN</b>	Canada
<b>CEPA</b>	Canadian Environmental Protection Act
<b>CERCLA</b>	Comprehensive Environmental Response – Compensation and Liability Act
<b>CFR</b>	Code of Federal Regulations
<b>CMR</b>	carcinogenic-mutagenic-toxic for reproduction
<b>COD</b>	Chemical oxygen demand
<b>DIN</b>	German Institute for Standardization
<b>DMEL</b>	Derived minimum effect level
<b>DNEL</b>	Derived no effect level
<b>DOT</b>	Department of Transportation
<b>EC50</b>	half maximal effective concentration
<b>EPA</b>	Environmental Protection Agency
<b>ErC50</b>	Reduction of Growth Rate
<b>ERG</b>	Emergency Response Guide Book
<b>FDA</b>	Food and Drug Administration
<b>GHS</b>	Globally Harmonized System of Classification and Labelling of Chemicals (GHS)
<b>GLP</b>	Good Laboratory Practice
<b>GMO</b>	Genetic Modified Organism
<b>HCS</b>	Hazard Communication Standard
<b>HMIS</b>	Hazardous Materials Identification System
<b>IARC</b>	International Agency for Research on Cancer
<b>IATA</b>	International Air Transport Association
<b>IBC</b>	Intermediate Bulk Container
<b>ICAO-TI</b>	International Civil Aviation Organization- Technical Instructions
<b>ICCA</b>	International Council of Chemical Association
<b>ID</b>	Identification number
<b>IMDG</b>	International Maritime Dangerous Goods
<b>IUPAC</b>	International Union of Pure and Applied Chemistry
<b>ISO</b>	International Organization For Standardization
<b>LC50</b>	50 % Lethal Concentration
<b>LD50</b>	50 % Lethal Dose
<b>L(E)C50</b>	LC50 or EC50
<b>LOAEL</b>	Low est observed adverse effect level
<b>LOEL</b>	Low est observed effect level
<b>MARPOL</b>	International Convention for the Prevention of Pollution from Ships
<b>NFPA</b>	National Fire Protection Association
<b>NOAEL</b>	No observed adverse effect level
<b>NOEC</b>	no observed effect concentration
<b>NOEL</b>	no observed effect level
<b>o. c.</b>	open cup
<b>OECD</b>	Organisation for Economic Cooperation and Development
<b>OEL</b>	Occupational Exposure Limit
<b>OSHA</b>	Occupational Safety and Health Administration
<b>PBT</b>	Persistent, bioaccumulative, toxic
<b>PEC</b>	Predicted effect concentration
<b>PNEC</b>	Predicted no effect concentration
<b>RQ</b>	Reportable Quantity
<b>SDS</b>	Safety Data Sheet
<b>STOT</b>	Specific Target Organ Toxicity
<b>UN</b>	United Nations
<b>vPvB</b>	very persistent, very bioaccumulative
<b>voc</b>	volatile organic compounds
<b>WHMIS</b>	Workplace Hazardous Materials Information System
<b>WHO</b>	World Health Organization